



INSPECTION OPENING (IO) INTERFACE METHOD

SEWER MAY BE IN ROAD OR FOOTPATH AS SPECIFIED BY ARMIDALE REGIONAL COUNCIL

NOTES

1. LOCATE SEWERS AND INSPECTION OPENINGS (IO'S) AS SHOWN IN DESIGN DRAWINGS.
2. "AS SPECIFIED" MEANS AS SPECIFIED BY THE WATER AGENCY.
3. RAISE IO TO SURFACE IN ACCORDANCE WITH WATER AGENCY REQUIREMENTS.
4. CONNECTIONS AT 45° OR 90° MAY BE ACCEPTED WITH WATER AGENCY APPROVAL.

LEGEND

- IO ● INSPECTION OPENING (RAISED TO SURFACE)
-] SEALED BURIED CONNECTION POINT
- - - - FUTURE PROPERTY DRAIN
- · - · - PROPERTY BOUNDARY

Armidale <i>Dept of Public Infrastructure</i> Regional Council	SCALES N.T.S	APPROVED D. MAUNDER MANAGER ENGINEERING AND STANDARDS SUPPORT	31/08/2016 DATE	SHEET 1 OF 1	
	PROPERTY CONNECTION DETAILS SEWER IN ROAD RESERVE		SURV DRWN VC DES MW CHKD MW	AS SHEET SIZE A3	DRAWING No 010-021
			CADFILE 010-021.dwg	DATE 31/08/2016	